
PTFE PISTON SEAL JSPG



Advantages:

- No stick-slip effect when starting for smooth operation
- Low friction and high wear resistance ensure long service life
- Min. Static and dynamic friction coefficient ensure high speed
- Simple groove design, one-piece piston possible.
- Suitable for most hydraulic fluids
- Available for all cylinder diameter up to 500 mm

ITEM	OD	ID	H
SPG	80	70	4
SPG	90	80	4
SPG	40	30	4.3
SPG	50	40	4.3
SPG	60	50	4.3
SPG	50	39	4.9
SPG	60	49	4.9
SPG	70	59	4.9
SPG	80	59	4.9
SPG	90	79	5.9
SPG	90		6.1
SPG	100		6.1
SPG	110		6.1
SPG	140		6.1

SPG	65	50	7.3
SPG	70	55	7.3
SPG	75	60	7.3
SPG	80	65	7.3
SPG	85	70	7.3
SPG	90	75	7.3
SPG	95	80	7.3
SPG	100	85	7.3
SPG	105	90	7.3
SPG	110	94	7.3
SPG	112	96	7.3
SPG	120	104	7.3
SPG	125	109	7.3
SPG	130	114	7.3
SPG	135	119	7.3
SPG	140	124	7.3
SPG	145	129	7.3
SPG	150	134	7.3
SPG	155	139	7.3
SPG	160	144	7.3
SPG	140		8
SPG	150		8
SPG	160		8
SPG	170		9
SPG	200	178	10.8
SPG	220	198	10.8
SPG	225	203	10.8

Product link : <https://www.jspseal.com/ptfe-piston-seal-jspg.html>