
4 PIECES PTFE PISTON SEAL JSPGW



Advantages:

- No stick-slip effect when starting for smooth operation
- Low friction and high wear resistance ensure long service life.
- Min. Static and dynamic friction coefficient ensure high speed
- Simple groove design, one-piece piston possible.
- Suitable for most hydraulic fluids
- Available for all cylinder diameter up to 500 mm

ITEM	OD	ID	H
JSPGW	50	36	8.5
JSPGW	60	46	8.5
JSPGW	65	50	10.5
JSPGW	70	55	10.5
JSPGW	75	60	10.5
JSPGW	80	66	10.5
JSPGW	85	70	10.5
JSPGW	90	75	10.5
JSPGW	95	80	10.5
JSPGW	100	85	12
JSPGW	105	90	12
JSPGW	110	95	12
JSPGW	115	100	12

JSPGW	120	105	12
JSPGW	125	102	15.5
JSPGW	130	107	15.5
JSPGW	135	112	15.5
JSPGW	140	117	15.5
JSPGW	145	122	15.5
JSPGW	150	127	15.5
JSPGW	160	137	15.5
JSPGW	165	142	15.5
JSPGW	170	147	15.5
JSPGW	180	152	15.5
JSPGW	185	162	15.5
JSPGW	190	167	15.5
JSPGW	195	172	15.5
JSPGW	200	177	15.5
JSPGW	220	197	15.5
JSPGW	225	202	15.5
JSPGW	150	127	15.5
JSPGW	160	137	15.5
JSPGW	165	142	15.5
JSPGW	170	147	15.5
JSPGW	180	152	15.5
JSPGW	185	162	15.5
JSPGW	190	167	15.5
JSPGW	195	172	15.5
JSPGW	200	177	15.5
JSPGW	220	197	15.5
JSPGW	225	202	15.5
JSPGW	230	207	15.5
JSPGW	235	212	15.5
JSPGW	240	217	15.5
JSPGW	250	222	17
JSPGW	255	227	17
JSPGW	260	232	17
JSPGW	265	237	17
JSPGW	270	242	17
JSPGW	275	247	17
JSPGW	280	252	17
JSPGW	300	272	17
JSPGW	320	292	17

Product link : <https://www.jspseal.com/4-pieces-ptfe-piston-seal-jspgw.html>